

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 March 2004 (04.03.2004)

PCT

(10) International Publication Number
WO 2004/018986 A1

(51) International Patent Classification⁷: G01L 1/16,
A61B 5/11

(21) International Application Number:
PCT/FI2003/000604

(22) International Filing Date: 15 August 2003 (15.08.2003)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:
20021508 21 August 2002 (21.08.2002) FI

(71) Applicant and

(72) Inventor: RUOTOISTENMÄKI, Heikki [FI/FI]; Sam-
malkallionkuja 2 F 107, FIN-02210 Espoo (FI).

(74) Agent: LEITZINGER OY; Tammasaarenkatu 1, FIN-
00180 Helsinki (FI).

(81) Designated States (national): AE, AG, AL, AM, AT (util-
ity model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,

CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (util-
ity model), DE, DK (utility model), DK, DM, DZ, EC, EE
(utility model), EE, ES, FI (utility model), FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ,
LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO,
RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: FORCE OR PRESSURE SENSOR AND METHOD FOR APPLYING THE SAME



(57) Abstract: The invention relates to a force or pressure sensor and a method for applying the same. The pressure sensor comprises a substantially rigid, mechanical-load resistant frame (1), a flexible diaphragm (2) secured over its peripheral rim to the frame (1), and a piezoelectric sensor diaphragm (3) applied to the surface of the flexible diaphragm (2). The sensor diaphragm (3) loading element comprises a substantially rigid, mechanical-load resistant cover (4), having its protrusion or shoulder (4a) bearing against a middle section of the flexible diaphragm (2) and thereby prestressing the flexible diaphragm (2) and the piezoelectric sensor diaphragm (3) attached thereto. The frame (1) and the cover (4) define therebetween a closed, hermetically sealed housing chamber, the flexible diaphragm (2) and the piezoelectric sensor diaphragm (3) being located therein. The placement of one or more responsive, yet load-resistant sensors in contact with a bed enables measuring a sleeping or lying person for his or her heart rate and respiratory amplitude, as well as frequency.